NSN 5320-01-209-9478

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-209-9478 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.375 inches and 2.395 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.436 inches and 0.437 inches **Shank Style: Head Major Diameter:** Between 0.641 inches and 0.676 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.438 inches Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5320-01-209-9478

Pin-rivet - Page 2 of 2



			on:	

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.