NSN 5320-01-210-2324

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-210-2324

Fastener Length:
0.366 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.386 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.156 inches and 0.220 inches
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
112000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Single action fastener installed with a single action tool
Material:
Steel
Material Specification:
Astm a331 assn standard single material response
Surface Treatment:
Cadmium stem or aluminum stem
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-c-83488 spec.