## NSN 5320-01-210-8405

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-210-8405 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.565 inches and 0.585 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment Specification:** 305, type 1, blue mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5320-01-210-8405

Pin-rivet - Page 2 of 2



Fiig:

A528u0