## NSN 5320-01-211-1556



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-211-1556 Fastener Length: 0.991 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** 0.386 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.781 inches and 0.845 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 112000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Single action fastener installed with a single action tool Material: Steel **Material Specification:** Astm a331 assn standard single material response **Surface Treatment:** Cadmium stem or aluminum stem **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-83488 spec.