NSN 5320-01-211-5082



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-211-5082 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.108 inches and 1.128 inches **Head Style:** Err-090 **Head Height:** Between 0.042 inches and 0.050 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.298 inches and 0.312 inches **Grip Length:** Between 0.751 inches and 0.812 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 156000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4450 professional/industrial association standard Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-211-5082

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0