NSN 5320-01-212-0163

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-212-0163

Thread Class.
Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.387 inches and 0.390 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.450 inches
Expansion Device:
Threaded mandrel
Grip Length:
0.375 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
0.250 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Special Features:
Furnished without bolt
Heat Treatment:
Annealed sleeve
Material:
Steel comp 305 or steel comp xm-7 or steel comp 302 sleeve
Material Specification:
Qq-s-763 federal specification 1st material response or astm a493 assn standard 2nd material response sleeve
Surface Treatment:
Cadmium expander
Surface Treatment Specification:
Qq-p-416 type 1 cl 2 federal specification single treatment response expander
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:

NSN 5320-01-212-0163

Blind Rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A040a0