## NSN 5320-01-212-2008

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-212-2008

Fastener Length:
1.178 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.213 inches and 0.215 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.386 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.969 inches and 1.032 inches
Shear Strength:
3450 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 8740 stem
Material Specification:
Ams 5737 assn standard single material response mechanical lock
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-f-81177 military specification single treatment response
Supplementary Features:
Stem cadmium coat unbrigthened cyanide specified
Specification Data:
81755-c9502 manufacturers specification control and 29666-osb100-t manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.
Fiig:
A040a0
Mil-std (military Standard):
Mil-f-81177 spec.