

View Online at <https://aerobasegroup.com/nsn/5320-01-212-2008>

**Fastener Length:**

1.178 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.213 inches and 0.215 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.386 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.969 inches and 1.032 inches

**Shear Strength:**

3450 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8740 stem

**Material Specification:**

Ams 5737 assn standard single material response mechanical lock

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-f-81177 military specification single treatment response

**Supplementary Features:**

Stem cadmium coat unbrighened cyanide specified

**Specification Data:**

81755-c9502 manufacturers specification control and 29666-osb100-t manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-f-81177 spec.