NSN 5320-01-213-3706

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-213-3706 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.010 inches and 1.030 inches **Head Style:** Err-090 **Head Height:** Between 0.077 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.630 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.250 inches **Special Features:** Furnished with one collar Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and aluminum alloy **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-213-3706

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0