## NSN 5320-01-214-3775

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-214-3775 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.135 inches and 1.155 inches **Head Style:** Err-090 **Head Height:** Between 0.077 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.415 inches and 0.440 inches **Grip Length:** 0.755 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-4140 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5320-01-214-3775

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.