NSN 5320-01-214-5105

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-214-5105

view Offilite at https://aerobasegroup.com/hist//3020-01-214-3103
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.178 inches and 0.180 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.332 inches
Expansion Device:
Threaded stem
Grip Length:
Between 0.720 inches and 0.781 inches
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c nut
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4140 or steel comp 8740 or steel comp 4130 nut
Material Specification:
Qq-s-763 federal specification 1st material response or ams 5639 assn standard 1st material response or ams 5641 assn standard 2nd
material response or astm a582 assn standard 3rd material response sleeve
Surface Treatment:
Passivate and cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type 2, cl2 federal specification single treatment response nut
Specification Data:
80205-nas1750 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0

Mil-s-5626 spec.

Mil-std (military Standard):