# NSN 5320-01-215-0141

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-215-0141

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.274 inches and 0.276 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

0.507 inches

#### **Expansion Device:**

Threaded stem

#### Grip Length:

Between 1.095 inches and 1.156 inches

#### Hardness Rating:

39.0 rockwell c and 43.0 rockwell c nut

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130 nut

## Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military

specification 3rd material response nut

## Surface Treatment:

Passivate and cadmium sleeve

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response nut

#### **Specification Data:**

80205-nas1750 professional/industrial association standard

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A040a0

#### Mil-std (military Standard):

Mil-s-5626 spec.