## NSN 5320-01-215-7356



Tubular Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-215-7356 Fastener Length: 0.562 inches **Head Style:** Countersunk w/ reverse chamfer **Head Height:** Between 0.053 inches and 0.067 inches **Hole Diameter:** Between 0.173 inches and 0.183 inches **Shank Diameter:** Between 0.244 inches and 0.252 inches **Shank Style:** Tubular **Head Major Diameter:** 0.478 inches Hole Depth: 0.219 inches **Shear Strength:** 35000 double pounds per square inch **Countersink Angle:** Between 148.0 degrees and 150.0 degrees **Special Features:** Optional tapered hole **Heat Treatment:** Quarter hard Material: Copper alloy 260 or copper alloy 270 **Material Specification:** Qq-w-321 1/4 hard federal specification all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-f-495 military specification 1st treatment response **Specification Or Standard:** 13 type and f grade Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A040a0

## NSN 5320-01-215-7356

Tubular Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-f-495 spec.