## NSN 5320-01-216-0345

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-216-0345 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.223 inches and 1.243 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.530 inches and 0.565 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.693 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5320-01-216-0345

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.