

View Online at <https://aerobasegroup.com/nsn/5320-01-217-0800>

**Fastener Length:**

Between 1.020 inches and 1.040 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.062 inches and 0.070 inches

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.250 inches and 0.272 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.844 inches and 0.907 inches

**Min. Tensile Strength (psi):**

112000 pounds per square inch

**Hardness Rating:**

48.0 rockwell c bolt and 53.0 rockwell c bolt

**Shear Strength:**

2340 single pounds per square inch

**Material:**

Steel comp 8740 bolt

**Material Specification:**

Mil-s-6049 federal specification single material response bolt

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl2 federal specification all treatment responses

**Specification Data:**

96906-ms90354s0514 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.