NSN 5320-01-217-4064



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-217-4064 Fastener Length: Between 0.365 inches and 0.385 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.004 inches and 0.006 inches **Shank Diameter:** Between 0.249 inches and 0.252 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** 0.3948 inches **Head Minor Diameter:** Between 0.316 inches and 0.326 inches **Countersink Height:** 0.060 inches **Shear Strength:** 26000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Heat Treatment:** T-4 solution heat treated Material: Aluminum alloy 2117 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-std (military Standard): Mil-a-8625 spec.

A040a0