

View Online at <https://aerobasegroup.com/nsn/5320-01-217-5257>

Fastener Length:

1.569 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2890 inches and 0.2910 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.507 inches

Expansion Device:

Threaded stem

Lubrication:

Carbo wax or grease film or cetyl alcohol or dry film

Grip Length:

Between 0.782 inches and 0.844 inches

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 bolt

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response nut

Surface Treatment:

Passivate or cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification 1st treatment response or nas 672 assn standard 2nd treatment response and qq-p-416 federal specification 2nd treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.