

View Online at <https://aerobasegroup.com/nsn/5320-01-217-6093>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.990 inches and 1.010 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.098 inches and 0.112 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3266 inches and 0.3276 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.472 inches and 0.502 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.495 inches and 0.505 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

9200 pounds per square inch

**Thread Size:**

0.312 inches

**Shear Strength:**

16000 double pounds per square inch

**Material:**

Steel

**Material Specification:**

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 ty1 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.