
NSN 5320-01-217-6094

Pin-rivet - Page 1 of 2

Thread Class:

Unjc





3a **Thread Direction: Right-hand** Fastener Length: Between 1.404 inches and 1.434 inches Head Style: Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches Shank Diameter: Between 0.1625 inches and 0.1635 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 1.077 inches and 1.087 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2400 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.164 inches Shear Strength: 5570 double pounds per square inch Material: Steel **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams2416 assn standard single treatment response **Thread Series Designator:**

NSN 5320-01-217-6094

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

