NSN 5320-01-218-0720

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-218-0720

Fastener Length:
Between 0.802 inches and 0.822 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.004 inches and 0.006 inches
Shank Diameter:
Between 0.249 inches and 0.252 inches
Shank Style:
Straight
Head Major Diameter:
0.3948 inches
Head Minor Diameter:
Between 0.316 inches and 0.326 inches
Countersink Height:
0.060 inches
Shear Strength:
33000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2017
Material Specification:
Qq-a-430, t4 federal specification single material response
Surface Treatment:
Anodize or oxide film
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-a-8625 spec.