NSN 5320-01-218-3263

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-218-3263

Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.289 inches and 0.291 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.507 inches
Expansion Device:
Serrated stem-type w
Lubrication:
Grease film or dry film or wax or cetyl alcohol
Grip Length:
Between 0.657 inches and 0.719 inches
Min. Tensile Strength (psi):
18000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c nut
Countersink Angle:
100.0 degrees
Material:
Steel comp 4140 or steel comp 8740 or steel comp 4130 nut
Material Specification:
Qq-s-763 federal specification 1st material response or ams 5639 assn standard 1st material response or ams 5641 assn standard 2nd
material response or astm a582 assn standard 3rd material response sleeve
Surface Treatment:
Passivate or cadmium sleeve
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0

Mil-s-5626 spec.

Mil-std (military Standard):