

View Online at <https://aerobasegroup.com/nsn/5320-01-218-3263>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.289 inches and 0.291 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.507 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Grease film or dry film or wax or cetyl alcohol

Grip Length:

Between 0.657 inches and 0.719 inches

Min. Tensile Strength (psi):

18000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c nut

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130 nut

Material Specification:

Qq-s-763 federal specification 1st material response or ams 5639 assn standard 1st material response or ams 5641 assn standard 2nd material response or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Passivate or cadmium sleeve

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.