

View Online at <https://aerobasegroup.com/nsn/5320-01-218-3820>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.753 inches and 0.773 inches

**Head Style:**

Err-090

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3765 inches and 0.3813 inches

**Lubrication:**

Solid film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.443 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0