
# NSN 5320-01-218-7556

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.598 inches and 1.638 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.042 inches and 0.050 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.298 inches and 0.312 inches

### Grip Length:

Between 1.251 inches and 1.312 inches

### Thready Qty Per Inch (tpi):

32

### Thread Size:

0.190 inches

### Shear Strength:

156000 single pounds per square inch

#### Material:

Steel comp h11

### **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

### Surface Treatment Specification:

Ams 2416 assn standard single treatment response

### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas4450 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-218-7556

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

