

View Online at <https://aerobasegroup.com/nsn/5320-01-218-9892>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.000 inches and 1.020 inches

Head Style:

Err-090

Head Height:

Between 0.093 inches and 0.105 inches

Width Between Flats:

Between 0.1895 inches and 0.1930 inches

Shank Diameter:

Between 0.436 inches and 0.437 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.380 inches

Hardness Rating:

45.0 rockwell c and 48.0 rockwell c

Thread Size:

0.438 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2, class 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.