
## NSN 5320-01-219-5443

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.010 inches and 1.030 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Grip Length:

0.630 inches

Thready Qty Per Inch (tpi):

28

## Hardness Rating:

45.0 rockwell c and 48.0 rockwell c

#### **Thread Size:**

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp h11

## **Material Specification:**

Ams6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Mil-c-8837, type 2, class 2 military specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-219-5443

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.

