

View Online at <https://aerobasegroup.com/nsn/5320-01-221-6873>

Thread Class:

Lh

Thread Direction:

Right-hand

Fastener Length:

1.220 inches

Head Style:

Flat fillister

Head Height:

Between 0.058 inches and 0.070 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.411 inches and 0.421 inches

Tip Diameter:

0.273 inches

Expansion Device:

Break stem

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.814 inches and 0.875 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

43.5 rockwell c and 46.5 rockwell c nut

Thread Size:

0.250 inches

Special Features:

Fastener length given is installed dimension

Material:

Steel comp 8740 nut

Material Specification:

Ams5639 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification 5th treatment response sleeve

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.