NSN 5320-01-221-6873

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-221-6873

Thread Class:
Lh
Thread Direction:
Right-hand
Fastener Length:
1.220 inches
Head Style:
Flat fillister
Head Height:
Between 0.058 inches and 0.070 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
Between 0.411 inches and 0.421 inches
Tip Diameter:
0.273 inches
Expansion Device:
Break stem
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.814 inches and 0.875 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
43.5 rockwell c and 46.5 rockwell c nut
Thread Size:
0.250 inches
Special Features:
Fastener length given is installed dimension
Material:
Steel comp 8740 nut
Material Specification:
Ams5639 assn standard 3rd material response sleeve
Surface Treatment:
Cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type ii, class 3 federal specification 5th treatment response sleeve
Thread Series Designator:
Uns
Shelf Life:
N/a

NSN 5320-01-221-6873

Blind Rivet - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.