

View Online at <https://aerobasegroup.com/nsn/5320-01-221-7110>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Fastener Length:**

1.047 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.044 inches and 0.056 inches

**Shank Diameter:**

0.222 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.328 inches and 0.339 inches

**Expansion Device:**

Threaded mandrel

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.626 inches and 0.688 inches

**Hardness Rating:**

43.5 rockwell c and 46.5 rockwell c nut

**Thread Size:**

0.138 inches

**Material:**

Steel comp 8740 nut

**Material Specification:**

Mil-s-6049 uns g87400 military specification single material response nut

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses sleeve

**Supplementary Features:**

Oversize tapered panhead blind fastener; nut modified class 2b lh thd

**Thread Series Designator:**

Unf

**Specification Data:**

92215-va213 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.