

View Online at <https://aerobasegroup.com/nsn/5320-01-221-7114>

Thread Class:

Lh

Thread Direction:

Right-hand

Fastener Length:

0.992 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.306 inches

Tip Diameter:

0.211 inches

Expansion Device:

Break stem

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.564 inches and 0.625 inches

Thready Qty Per Inch (tpi):

40

Hardness Rating:

43.5 rockwell c and 46.5 rockwell c nut

Thread Size:

0.188 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Fastener length given is installed dimension

Material:

Steel comp 8740 nut

Material Specification:

Mil-s-6049 military specification 2nd material response nut

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification 3rd treatment response sleeve

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.