## NSN 5320-01-222-0207

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-222-0207 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.940 inches and 0.960 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style: Head Major Diameter:** Between 0.3765 inches and 0.3813 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.620 inches and 0.630 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-222-0207

Pin-rivet - Page 2 of 2



Fiig:

A528u0