NSN 5320-01-223-3625

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-223-3625

| Fastener Length: |
|--|
| 1.781 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.258 inches and 0.260 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| 0.507 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 1.531 inches and 1.595 inches |
| Hardness Rating: |
| 48.0 rockwell c stem and 53.0 rockwell c stem |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 6150 |
| or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 |
| Material Specification: |
| Astm a331 assn standard single material response |
| Surface Treatment: |
| Cadmium stem or aluminum alloy stem |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 2 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-f-81177 spec. |
| |