## NSN 5320-01-224-2428

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-224-2428 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.315 inches and 1.335 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.381 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.005 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-224-2428

Pin-rivet - Page 2 of 2



Fiig:

A528u0