

View Online at <https://aerobasegroup.com/nsn/5320-01-224-9158>

**Identification Code Color:**

Green

**Fastener Length:**

1.365 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.386 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 1.156 inches and 1.220 inches

**Min. Tensile Strength (psi):**

2100 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

3450 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4027 sleeve or steel comp 4037 sleeve or steel comp 4130 sleeve or steel comp 4140 sleeve or steel comp 4150 sleeve or steel comp 4340 sleeve or steel comp 4620 sleeve or steel comp 4815 sleeve or steel comp 8615 sleeve or steel comp 8620 sleeve or steel comp 8630 sleeve or steel comp 8640 sleeve or steel comp 8740 sleeve

**Material Specification:**

Fed 66 federal standard 1st material response mechanical lock or federal 66 federal standard 2nd material response mechanical lock or federal 66 federal standard 3rd material response mechanical lock or federal 66 federal standard 4th material response mechanical lock or federal 66 federal standard 5th material response mechanical lock or ams5737 assn standard 6th material response mechanical lock or ams5690 assn standard 7th material response mechanical lock

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0