

View Online at <https://aerobasegroup.com/nsn/5320-01-224-9158>

Identification Code Color:

Green

Fastener Length:

1.365 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.386 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 1.156 inches and 1.220 inches

Min. Tensile Strength (psi):

2100 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

3450 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4027 sleeve or steel comp 4037 sleeve or steel comp 4130 sleeve or steel comp 4140 sleeve or steel comp 4150 sleeve or steel comp 4340 sleeve or steel comp 4620 sleeve or steel comp 4815 sleeve or steel comp 8615 sleeve or steel comp 8620 sleeve or steel comp 8630 sleeve or steel comp 8640 sleeve or steel comp 8740 sleeve

Material Specification:

Fed 66 federal standard 1st material response mechanical lock or federal 66 federal standard 2nd material response mechanical lock or federal 66 federal standard 3rd material response mechanical lock or federal 66 federal standard 4th material response mechanical lock or federal 66 federal standard 5th material response mechanical lock or ams5737 assn standard 6th material response mechanical lock or ams5690 assn standard 7th material response mechanical lock

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0