

View Online at <https://aerobasegroup.com/nsn/5320-01-225-7791>

**Fastener Length:**

Between 0.670 inches and 0.730 inches

**Head Style:**

Universal

**Head Height:**

Between 0.080 inches and 0.090 inches

**Shank Diameter:**

Between 0.188 inches and 0.192 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.365 inches and 0.385 inches

**Expansion Device:**

Break head

**End Application:**

Uw/s: aircraft, b-2 bomber (atb); missile, vehicle mounted stinger (avenger); sentinel radar system; aircraft, hx unique; thermal imagery - mctns; low altitude navigation & targeting infrared system (lantirn); aircraft, galaxy c-5

**Grip Length:**

Between 0.501 inches and 0.562 inches

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Iron alloy 660 collar

**Specification Data:**

81349--7885/2-6-9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0