# NSN 5320-01-227-1495

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-227-1495



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.411 inches and 1.436 inches

## Head Style:

Err-090

#### Shank Diameter:

0.3403 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.554 inches

## Tip Diameter:

0.3245 inches

# Lubrication:

Cetyl alcohol and dry film

## Grip Length:

Between 0.927 inches and 0.942 inches

# Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.3125 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-227-1495

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

