

View Online at <https://aerobasegroup.com/nsn/5320-01-228-5181>

**Fastener Length:**

Between 1.413 inches and 1.443 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.376 inches and 0.396 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 1.219 inches and 1.282 inches

**Min. Tensile Strength (psi):**

2100 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

3450 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4037 sleeve

**Material Specification:**

Astm a331 assn standard single material response sleeve

**Surface Treatment:**

Cadmium stem

**Specification Data:**

96906-ms90353 government standard and 29666-b100-t manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0