

View Online at <https://aerobasegroup.com/nsn/5320-01-229-0013>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.615 inches and 1.635 inches

Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.130 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

45.0 rockwell c and 48.0 rockwell c

Thread Size:

0.312 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, ty2, cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.