NSN 5320-01-229-8190

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-229-8190

| Head Style: |
|---|
| Shovel |
| Head Height: |
| Between 0.022 inches and 0.032 inches |
| Shank Diameter: |
| Between 0.139 inches and 0.143 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| Between 0.210 inches and 0.230 inches |
| Countersink Height: |
| 0.011 inches |
| Expansion Device: |
| Plain stem-type t |
| Grip Length: |
| Between 0.063 inches and 0.125 inches |
| Special Features: |
| 100 degrees countersunk head |
| Material: |
| Steel comp 632 stem |
| Material Specification: |
| Ams5657 assn standard single material response stem |
| Surface Treatment: |
| Chromate sleeve |
| Surface Treatment Specification: |
| Qq-p-416, type 1, cl 2 federal specification single treatment response stem |
| Specification Data: |
| 80205-nas9306 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |

Mil-c-5541 spec.