
# NSN 5320-01-229-8198

Pin-rivet - Page 1 of 1



## Head Style:

Err-090

## Head Height:

Between 0.128 inches and 0.147 inches

## Shank Diameter:

Between 0.2635 inches and 0.2650 inches

#### Shank Style:

Pin-rivet, multiple grooved

#### Head Major Diameter:

Between 0.390 inches and 0.430 inches

Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.470 inches and 0.531 inches

#### Features Provided:

Casehardened

## Min. Tensile Strength (psi):

1600000 pounds per square inch

## Hardness Rating:

77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

## Shear Strength:

95000 single pounds per square inch

#### Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

#### **Material Specification:**

Astm a547 assn standard all material responses

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Specification Data:**

80205-nas1468 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A528u0

