NSN 5320-01-230-0016

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-230-0016

| Fastener Length: |
|--|
| 1.100 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.435 inches and 0.437 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| 0.900 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.719 inches and 0.782 inches |
| Hardness Rating: |
| 48.0 rockwell c stem and 53.0 rockwell c stem |
| Shear Strength: |
| 112000 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 8740 stem |
| Material Specification: |
| Astm a331 assn standard single material response stem |
| Surface Treatment: |
| Aluminum stem |
| Surface Treatment Specification: |
| Mil-c-83488 military specification single treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-c-83488 spec. |