## NSN 5320-01-231-1349

Blind Rivet - Page 1 of 1

**Surface Treatment Specification:** 

Shelf Life:

**Unit Of Measure:** 

Demilitarization:

N/a

No Fiig: A040a0

Qq-p-416, ty2, cl2 federal specification single treatment response sleeve



View Online at https://aerobasegroup.com/nsn/5320-01-231-1349 **Identification Code Color:** Green **Fastener Length:** 0.553 inches **Head Style:** Tapered pan **Head Height:** Between 0.125 inches and 0.135 inches **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.305 inches and 0.332 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.344 inches and 0.407 inches **Hardness Rating:** 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 **Material Specification:** Astm a331 assn standard single material response **Surface Treatment:** Cadmium stem