## NSN 5320-01-231-3326

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-231-3326

Identification Code Color:
Green
Fastener Length:
0.553 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.386 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.344 inches and 0.407 inches
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
112000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 6150
or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740
Material Specification:
Astm a331 assn standard all material responses
Surface Treatment:
Cadmium stem or aluminum stem
Surface Treatment Specification:
Qq-p-416 type 2 cl2 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-c-83488 spec.