# NSN 5320-01-231-5255

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-231-5255



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.756 inches and 1.781 inches

# Head Style:

Err-090

#### Head Height:

Between 0.082 inches and 0.094 inches

#### Shank Diameter:

0.4381 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.628 inches and 0.642 inches

#### **Tip Diameter:**

0.4128 inches

# Grip Length:

1.317 inches

# Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

180000 pounds per square inch

## **Thread Size:**

0.375 inches

## Shear Strength:

108000 single pounds per square inch

## Material:

Steel comp 8740

## Material Specification:

Mil-s-6049 military specification single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-231-5255

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

