## NSN 5320-01-231-5943

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-231-5943

Identification Code Color:
Green
Fastener Length:
0.530 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.162 inches and 0.164 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.333 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.344 inches and 0.407 inches
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Shear Strength:
112000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4027 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615
or steel comp 8620 or steel comp 8640 or steel comp 8740 or steel comp 4130 or steel comp 8630
Material Specification:
Astm a331 assn standard all material responses
Surface Treatment:
Cadmium stem or aluminum stem
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-c-83488 spec.