

View Online at <https://aerobasegroup.com/nsn/5320-01-231-6939>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.370 inches and 0.380 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

6130 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment Specification:

Hi-shear specification 305, type 1, blue mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0