NSN 5320-01-231-7532

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-231-7532

Green Length: O,777 inches Head Style: Tapered pan Head Height: Between 0.652 inches and 0.070 inches Shank Diameter: Between 0.652 inches and 0.164 inches Shank Diameter: Between 0.652 inches and 0.164 inches Shank Diameter: Between 0.2550 inches and 0.164 inches Shank Diameter: Between 0.2550 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Head Major Diameter: Between 0.531 inches and 0.595 inches Headress Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material's Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material's Specification: Astm a331 asan standard single material response Surface Treatment Specification: Qq-p-416, ty2, ti2 federal specification single treatment response sleeve Sheft Life: Na Unit Of Measure:	Identification Code Color:
D.717 inches Head Style: Tapered pan Head Height: Between 0.062 inches and 0.070 inches Shank Diameter: Between 0.162 inches and 0.164 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Heardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8815 or steel comp 8620 or steel comp 8830 or steel comp 8640 or steel comp 8740 Material: Surface Treatment: Cadmium stem Surface Treatment Specification: Qrtp-416, ty2, ct2 federal specification single treatment response sleeve Shelf Life: Na Unit Of Measure: Demilitarization: No Filig:	Green
Head Height: Petween 0.062 inches and 0.070 inches Petween 0.062 inches and 0.070 inches Petween 0.162 inches and 0.170 inches Petween 0.162 inches and 0.164 inches Phank Diameter: Petween 0.162 inches and 0.164 inches Phank Diameter: Petween 0.162 inches and 0.164 inches Phank Diameter: Petween 0.250 inches and 0.272 inches Petween 0.250 inches and 0.295 inches Petween 0.250 inches and 0.595 inches Petween 0.251 inches and 0.595 inches Petween 0.250 inches Petween 0.251 inch	Fastener Length:
Tapered pan Head Height: Between 0.062 inches and 0.070 inches Shank Diameter: Between 0.162 inches and 0.164 inches Shank Style: Between 0.162 inches and 0.164 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Sorrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Sheft Life: N/a Unit of Measure:	0.717 inches
Head Height: Between 0.062 inches and 0.070 inches Shank Diameter: Between 0.162 inches and 0.164 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4815 or steel comp 8815 or steel comp 8820 or steel comp 8830 or steel comp 8640 or steel comp 8740 Material: Steel comp 4027 or steel comp 8830 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Head Style:
Between 0.062 inches and 0.070 inches Shank Diameter: Between 0.162 inches and 0.164 inches Shank Style: Schiplugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.251 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 5.30 rockwell c stem Shear Strength: 11.2000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Tapered pan
Shank Diameter: Between 0.162 inches and 0.164 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4820 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, ct2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure:	Head Height:
Between 0.162 inches and 0.164 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 asen standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.062 inches and 0.070 inches
Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure:	Shank Diameter:
Self-pluging mechanically locked stem Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8630 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 asan standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Between 0.162 inches and 0.164 inches
Head Major Diameter: Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, ct2 federal specification single treatment response sleeve Sheft Life: Na Unit Of Measure: Demilitarization: No Fig:	Shank Style:
Between 0.250 inches and 0.272 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Self-plugging mechanically locked stem
Expansion Device: Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Head Major Diameter:
Serrated stem-type w Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.250 inches and 0.272 inches
Grip Length: Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, c 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Expansion Device:
Between 0.531 inches and 0.595 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Serrated stem-type w
Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Grip Length:
48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.531 inches and 0.595 inches
Shear Strength: 112000 single pounds per square inch Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hardness Rating:
Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	48.0 rockwell c stem and 53.0 rockwell c stem
Material: Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Shear Strength:
Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	112000 single pounds per square inch
or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 4027 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4620 or steel comp 4815 or steel comp 8615
Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740
Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
Cadmium stem Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Astm a331 assn standard single material response
Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Qq-p-416, ty2, cl2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium stem
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-p-416, ty2, cl2 federal specification single treatment response sleeve
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A040a0	Fiig:
	A040a0