
## NSN 5320-01-231-7544

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.785 inches and 1.805 inches

## Head Style:

Err-090

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Err-090

#### Head Major Diameter:

Between 0.7556 inches and 0.7604 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

1.255 inches

## Thready Qty Per Inch (tpi):

24

### Thread Size:

0.375 inches

## Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

### **Special Features:**

White paint on head

#### Material:

Steel comp xm-13

### Material Specification:

Ams5629 military specification single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-231-7544

Pin-rivet - Page 2 of 2

Fiig:

A528u0

Mil-std (military Standard):

spec.

