NSN 5320-01-232-3558

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-232-3558

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.885 inches and 0.910 inches
Head Style:
Err-090
Head Height:
Between 0.379 inches and 0.389 inches
Shank Diameter:
0.2636 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
Between 0.058 inches and 0.070 inches
Tip Diameter:
0.2538 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 0.552 inches and 0.567 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.2500 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1728 professional/industrial association standard

NSN 5320-01-232-3558

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0